




## Products Features

- ▶ Excellent dual telecentric design for high resolution image result.
- ▶ Suitable for 4/3" 16K 3.5um M/F mount industry camera.
- ▶ Customize design is available.

## Model Description



## Parameter

Sensor size	Item No	FOV (Φmm)	Mag.(x)	WD(mm)	F/#	Image MTF30 (lp/mm)	DoF (mm)	Image distortion (% max)	Telecentric degree (°max)	I/O (mm)	Total length (mm)	Mount	N.W. (kg)	NA
Φ59	SBS-SCJ16K-228-0.738	80	0.738	228±4	9.9	>85	±1.6@F22	<0.1	<0.1	580±4	340	M72	3.351	0.02656
	SBS-SCJ16K-208-0.656	90	0.656	208±3	15.4	>50	±1.3@F20	<0.1	<0.1	595±3	375.0	M72	3.1	0.02125
	SBS-SCJ16K-263-0.536	110	0.536	263±4	12.6	>60	±2.8@F20	<0.1	<0.1	703±4	427.6	M72	4.141	0.03717
	SBS-SCJ16K-273-0.492	120	0.492	273±5	11.6	>75	±3.6@F22	<0.1	<0.1	724±5	439.3	M72	-	0.02125
	SBS-SCJ16K-288-0.434	136	0.434	288±5	10.7	>80	±4.2@F20	<0.1	<0.1	813±5	512.6	M72	5.681	0.02125
	SBS-SCJ16K-300-0.393	150	0.393	300±5	19.8	>45	±5.1@F20	<0.1	<0.1	794±5	482.0	M72	7.1	0.00992
	SBS-SCJ16K-318-0.347	170	0.347	318±5	8.7	>90	±5.3@F16	<0.1	<0.1	874±5	543.9	M72	7.961	0.02032
	SBS-SCJ16K-330-0.311	190	0.311	330±5	8.7	>100	±6.6@F16	<0.1	<0.1	913±5	571.2	M72	11.1	0.0179
	SBS-SCJ16K-372-0.273	216	0.273	372±5	8.7	>95	±8.6@F16	<0.1	<0.1	1051±5	666.7	M72	15.2	0.01574
	SBS-SCJ16K-410-0.246	240	0.246	410±6	8.7	>100	±14.6@F22	<0.1	<0.1	1135±6	712.5	M72	20.5	0.01417
	SBS-SCJ16K-338-0.229	258	0.229	338±5	8.7	>100	±12.2@F16	<0.1	<0.1	940±5	589.9	M72	-	0.01318
SBS-SCJ16K-465-0.197	300	0.197	465±6	9.0	>95	±20.6@F20	<0.1	<0.1	1268±6	791.0	M72	48.0	0.01091	